


90

GOMITO A 90°




CODICE	Tubo d'acciaio			Pressione Massima			Dimensioni aprox.	Peso aprox. (grs)
	DN	Pollici	Φext (mm)	Bar	Mpa	PSI	L (mm)	
609002/505	25	1"	33.7	34.50	3.45	500	57	237
609002/506	32	1 1/4"	42.4	34.50	3.45	500	70	414
609002/507	40	1 1/2"	48.3	34.50	3.45	500	70	483
609002/508	50	2"	60.3	34.50	3.45	500	83	652
609002/50B	65	2 1/2"	76.1	34.50	3.45	500	95	1153
609002/50A	80	3"	88.9	34.50	3.45	500	108	1607
609002/50C	100	4"	114.3	34.50	3.45	500	127	2661
609002/50H	125	5"	139.7	34.50	3.45	500	140	4091
609002/50K	150	6 1/2" O.D	165.1	34.50	3.45	500	165	5992
609002/50E	150	6"	168.3	34.50	3.45	500	165	6069
609002/50M	200	8"	219.1	34.50	3.45	500	197	11118
609002/50N	250	10"	273.0	34.50	3.45	500	229	24580
609002/50Q	300	12"	323.9	34.50	3.45	500	254	35523

2/5 - 2= Rosso - 5= Zincato

90 S

GOMITO A 90° STANDARD



CODICE	Tubo d'acciaio			Pressione Massima			Dimensioni aprox.	Peso aprox. (grs)
	DN	Pollici	Φext (mm)	Bar	Mpa	PSI	L (mm)	
6090S2/508	50	2"	60.3	20.70	2.07	300	70	578
6090S2/50B	65	2 1/2"	76.1	20.70	2.07	300	76	967
6090S2/50A	80	3"	88.9	20.70	2.07	300	86	1327
6090S2/50C	100	4"	114.3	20.70	2.07	300	101	2010
6090S2/50H	125	5"	139.7	20.70	2.07	300	124	3665
6090S2/50K	150	6 1/2" O.D	165.1	20.70	2.07	300	140	4824
6090S2/50E	150	6"	168.3	20.70	2.07	300	140	4995
6090S2/50M	200	8"	219.1	20.70	2.07	300	175	8466

2/5 - 2= Rosso - 5= Zincato